

## CX-D80H 600dpi Card Printer Introduction Sheet

Model Name		CX-80SR/D (300dpi)	CX-D80H (600dpi)
Printing Method	YMC, UV	Dye Sublimation	Dye Sublimation
	K	Resin	Resin
Thermal Head Resolution		300dpi	<b>600dpi</b>
Memory		16MB	<b>64MB</b>
Double Side/ Single Side Printing		CX-D80SR: Single Side CX-D80D: Double Side	<b>Only Double Side</b>
Printing Speed		Approx. 36 sec (YMCK Single)	<b>Approx. 31.0 sec (YMCK Single)</b>
Ink Ribbon	YMC-K (1,000 screens/roll)	YMC-K (1,000 screens/roll)	YMC-K (1,000 screens/roll)
	YMC-K-K (750 screens/roll)		(*1)
	YMC-K-UV (750 screens/roll)		(*1)
	YMC-K-PO (750 screens/roll)		(*1)
Retransfer Film		Transparent (1,000 screens/roll)	Transparent (1,000 screens/roll)
Outer Size		343mm(W)x411mm(H)x322mm(D)	343mm(W)x411mm(H)x322mm(D)
Weight		Approx. 13.5kg	Approx. 13.5kg
Driver Soft		Compatible only For CX-D80	<b>Compatible only for CX-D80H</b>
Operational Environment		Windows 2000,XP,VISTA,7,8	Windows XP,VISTA,7,8
Safety Standard		UL,CE,CCC	<b>UL,CE</b>
Option Unit		* Bend Remedy Unit (CF-7BR) * MG Encoding Unit (CF-7MGS) * IC Contact R/W (CF-7CRW) * IC Contact Case (CF-7CCS) * IC Contactless R/W bracket (CF-7CB)	* Bend Remedy Unit (CF-7BR) * MG Encoding Unit (CF-7MGS) * IC Contact R/W (CF-7CRW) * IC Contact Case (CF-7CCS) * IC Contactless R/W bracket (CF-7CB)

### Remarks of CX-D80H

- \* made-to-order item
- \* A leadtime is 3-4 months upon receipt of order.
- \* A minimum order quantity is 10 units
- \* CX-D80H can be used with CL-600S/D.
- \* A unit price is TBD ( **As an evaluation/demo unit, you can purchase 1 unit at JPY 295,000 just one time.**)
- (\*1) A firmware for YMCK-K, YMC-K-UV and YMC-K-PO will be updated in future.